

Certification holder :

Kurt Obermeier GmbH

Product trade name :

KORASIT KS2

Use category :

Preventiv treatment

Formulation type :

Hydrosoluble
Concentrate

Users category :

Industrials

The CTB-P+ certification attests to:

- ✓ **The efficacy of the product** to prevent the attacks of the wood (or wood-based products) by biological organisms destroying or altering its appearance.
- ✓ **The validation** of the product / process couple.
- ✓ **The maintenance of the product quality** by regular technical audits of the manufacture and the control on the production site.
- ✓ **The relevance of the technical information** from the product supplier.

Certificate n°: 502-23-2083-En

Cancel and replace certificate n° 502-22-2100

Date issue : 09/21/2023

Expiration date : 09/20/2026

nb of pages : 2

Le Directeur certification
Alain HOCQUET

KORASIT KS2

CERTIFICATION PRERQUISITE Health/ Environment acceptability according to REACH and CLP regulations

| | | |
|--------------------|--------------------------------------|--------|
| COMPOSITION (w/w) | Copper carbonate | 19,20% |
| | (Cu) | 10,56% |
| | DMPAP (quaternary ammonium compound) | 10,56% |

IMPREGNATION TREATMENT

CRITICAL VALUE (kg/m³)

| Use class | Without termites | | Anti termites (T) | |
|-------------------|------------------|----------|-------------------|----------|
| | Softwood | Hardwood | Softwood | Hardwood |
| 1 | 7,8 | 7,8 | 10,8 | 10,8 |
| 2 | 12,1 | 12,1 | 12,1 | 12,1 |
| 3.1 | 12,1 | 12,1 | 12,1 | 12,1 |
| 3.2 | 12,1 | 12,1 | 12,1 | 12,1 |
| 4 (retention 4) | 14,2 | 14,2 | 14,2 | 14,2 |
| 4 (retention 4Sp) | 23,7 | 23,7 | 23,7 | 23,7 |

BIOLOGICAL RISK COVERED*

Fungi: Brown rot
White rot
Soft rot

Insects: All beetles spp (I)

Termites: Antitermite (T) qualification

* according to EN 599-1

PROCESS

Vacuum pressure autoclave

USE DETAILS

Additifs: Korasilon Entschäumer EMA119 (0.1 -2.0%)
Korasit Farbpaste 5163 braun (pâte colorante Korasit® 5163 marron) (1.0%)
Korasit Farbpaste 5215 braun (pâte colorante Korasit® 5215)(0.5%)
Korasilon Entschäumer FGG 30 (0.01%)

Deep impregnation by autoclave : Certified compliant on softwood species